

MAHLE

Driven by performance

WIRELESS MOBILE COLUMN LIFT SYSTEM

In partnership with Gray, our wireless lift systems will lift a wide variety of vehicles allowing technicians to safely and efficiently complete preventative maintenance tasks to major component repair.

Manufactured by



CML-7

www.servicesolutions.mahle.com

ShopPRO®

SAFE AND EFFICIENT

The patented Gray Wireless Portable Lift System improves a shop's safety, productivity and flexibility. The wireless lift system family will lift a wide variety of vehicles allowing technicians to safely and efficiently complete preventative maintenance tasks to major component repair.

Features

HEAVY DUTY LIFTING CAPACITY.

14,000 lb (CML-7) and 19,000 lb (CML-9) per column capacity options. Wide base available in 19,000lb capacity (CML-9W)

INTELLIGENT.

Patented Wireless Smart Lift Technology

SIMPLE.

Tablet based touch screen with on-board manuals, videos and internet

ELECTRIC.

24 volt DC system

BROAD APPLICATION.

Heavy Duty through Light Duty vehicles.

FULLY ADJUSTABLE CARRIAGE.

12" forks supports wheel diameter from 5" to 24.5"

PATENT PENDING.

Down-stop visual safety system

ADJUSTABLE.

Lift height 69" (1753 mm)

485 80094 00 LIFT COLUMN CML-7 WIRELESS (7 TON)

485 80098 00 LIFT COLUMN CML-9 TON WIRELESS (9.5 TON)

485 80102 00 LIFT COLUMN CML-9W WIDE BASE (9.5 TON)

FEATURE COMPARISON	CML-7	CML-9	CML-9W
Certification	ALI Certified	ALI Certified	ALI Certified
Capacity (Each)	14,000 lb (6,350 kg)	19,000 lb (8,165 kg)	19,000 lb (8,165 kg)
Max. Hydraulic Operating Pressure	2,180 psi (15 MPa)	2,600 psi (17.9 MPa)	2,600 psi (17.9 MPa)
Min/Max Wheel Diameter	5 in / 24.5 in (127 mm / 622 mm)	5 in / 24.5 in (127 mm / 622 mm)	4 in (102mm) - No Max
Min (2)/Max (4) Lift Height	32 in / 69 in (813 mm / 1,753 mm)	32 in / 69 in (813 mm / 1,753 mm)	32 in / 69 in (813 mm / 1,753 mm)
Lift Speed (Max.Load)	60 in/min (1,524 mm/min)	60 in/min (1,524 mm/min)	60 in/min (1,524 mm/min)
Weight	1,485 lb (674 kg)	1,510 lb (685 kg)	1,575 lb (714 kg)
Height	88.5 in (2,248 mm)	88.5 in (2,248 mm)	88.5 in (2,248 mm)
Height at Full Lift	157.13 in (3,991 mm)	157.13 in (3,991 mm)	157.13 in (3,991 mm)
Operating Peak Power	4 HP (3 kW)	4 HP (3 kW)	4 HP (3 kW)
Operating Voltage	24 VDC Nominal	24 VDC Nominal	24 VDC Nominal
Charger Voltage Required	70-130 VAC @50-60 Hz	70-130 VAC @50-60 Hz	70-130 VAC @50-60 Hz