

MAHLE

Driven by performance

AXLE JACKS



This series of jacks is known throughout the industry as the most reliable and longest lasting lift system of its kind. Their compact and field-ready design and low starting height makes them ideal for shop use or road service work.

www.servicesolutions.mahle.com

ShopPRO[®]

Axle Jack

Four hydraulic axle jack options, three with a 25 ton capacity, and one at a 35 ton capacity.

FEATURES:

- Unique QuickLift® feature, internal design raises the ram to the load at a quicker rate of speed
- Low starting height of 8" allows for easy positioning and spotting underneath low profile vehicles
- Patent pending air ram retract feature allows the user to reset the ram back to minimum starting height without reconnecting the hose
- Short handled version ideal for road service work

ADDITIONAL FEATURES

Black Armor Coating™ Protects the ram from rust and corrosion to extend longevity of product

Anti-Corrosive System The distinctive design of the internal system protects the hydraulic system to extend product life



485 80051 00 CAJ-25 25 Ton Axle Jack
 485 80053 00 CAJ-25LP 25 Ton Axle Jack – Large Pad
 485 80052 00 CAJ-25S 25 Ton Axle Jack – Short Handle
 485 80054 00 CAJ-35 35 Ton Axle Jack

FEATURE COMPARISON

	CAJ-25	CAJ-25LP	CAJ-25S	CAJ-35
Capacity	50,000 lb (22,680 kg)	50,000 lb (22,680 kg)	50,000 lb (22,680 kg)	70,000 lb (31,751 kg)
Minimum Start Height	8 in (20 cm)	-	8 in (20 cm)	-
Maximum Lift Height	21 in (53 cm)	-	21 in (53 cm)	-
Power Source	Air/Hydraulic	-	Air/Hydraulic	-
Required Air Pressure	90 to 120 psi (6.2 to 8.3 bar)	-	90 to 120 psi (6.2 to 8.3 bar)	110 to 200 psi (7.7 to 13.8 bar)
Stroke	5.1 in (13 cm)	5.1 in (13 cm)	5.1 in (13 cm)	5.1 in (13 cm)
Extension Screw Adjustment	4.9 in (12 cm)	-	4.9 in (12 cm)	-
Frame Width	12 in (30 cm)	-	12 in (30 cm)	-
Frame Length	20 in (51 cm)	-	20 in (51 cm)	-
Wheel Diameter	8 in (20 cm)	-	8 in (20 cm)	-
Handle Length	53 in (135 cm)	-	23 in (58 cm)	-
Shipping Weight	124 lb (56 kg)	120 lb (54 kg)	124 lb (56 kg)	146 lb (66 kg)
Maximum Air Pressure	-	200 psi (13.8 bar)	-	-
Starting Height (SH)	-	8.7 in (22 cm)	-	-
SH w/ Short Lift Pad Extension	-	11 in (28 cm)	-	-
SH w/ Tall Lift Pad Extension	-	13.7 in (35 cm)	-	-
SH w/ Short and Tall Lift Pad Extensions	-	16 in (41 cm)	-	-
Lifting Height (LH)	-	13.6 in (35 cm)	-	-
LH w/ Short Lift Pad Extension	-	16.2 in (41 cm)	-	-
LH w/ Tall Lift Pad Extension	-	18.8 in (48 cm)	-	-
LH w/ Short and Tall Lift Pad Extensions	-	21.1 in (54 cm)	-	-
Lift Pad Diameter	-	3.5 in (9 cm)	-	-
Lift Pad Start Height	-	-	-	9.3 in (24 cm)
Lift Pad Start Height w/ Adapter	-	-	-	11.9 in (30 cm)
Screw Adjustment	-	-	-	5 in (13 cm)
Length (Handle Horizontal)	-	-	-	71 in (180 cm)
Width at Wheels	-	-	-	14.3 in (36 cm)
Overall Height (Handle Vertical)	-	-	-	58.5 in (149 cm)

10 Ton Bottle Jack for Ag Sprayer – Air Assist

Safely change the wheels on a sprayer with this 10 ton bottle jack.

FEATURES:

- 100% air operated
- Built-in vehicle support stand feature
- Multiple width saddle options
- Removeable handle
- Can be used in pairs with the air valve T-connector

485 80019 00

CBJ-10A 10 Ton Bottle Jack for Ag Sprayer – Air Assist

SPECIFICATIONS

Capacity 20,000 lb (9,072 kg)

Minimum Start Height 50 in (127 cm)

Minimum Start Height with Wide Saddle 50 in (126 cm)

Maximum Lift Height 68 in (172 cm)

Maximum Lift Height with Wide Saddle 67 in (169 cm)

Saddle Width 6.25 in (16 cm)

Wide Saddle Width 9.875 in (25 cm)

Pin Increment Positions 2.5 in (6.35 cm)

Stroke 9.625 (24 cm)

Width 26 in (66 cm)

Length 27.5 in (70 cm)

Total Weight 290 lb (132 kg)