

PERFORMANCE PACKED WITH VALUE

NEW & IMPROVED!
Updated Software
& Faster Recovery

The solution for high-quality A/C servicing equipment
at an economical price.



ACX1120H

ACX1150

ACX1150H

Optional Upgrades



- **ON-BOARD INTEGRATED THERMAL PRINTER.**

Print to USB (for standard paper) allows user to store “before and after” service information by vehicle and print information for the customer.

- **HOSE FLUSHING.**

- External on the ACX1120H and integrated internally on the ACX1150/1150H.

- **OPTIONAL DATABASE.**

- Reliable and high-quality vehicle database included for latest A/C service information. (ACX1150/1150H only)

- **TOUCH SCREEN DISPLAY.**

- Controlled by a 4.3” color touch screen for faster input (ACX1150/1150H only).



ArcticPRO® for Refrigerant R134A

Loaded with cost-saving features and the same superior system performance that you have come to expect with the ArcticPRO series; the ACX1120H, ACX1150 and ACX1150H keep your shop's bottom line in mind. Our newest software upgrades have enhanced unit performance by removing the requirement for multi-pass. Additionally, a larger capacity filter has been added that increases the efficiency of the refrigerant cleaning process and decreases service time!

Capable of servicing all passenger cars and trucks and equipped to accommodate hybrid vehicles, these ArcticPRO units also contain a high performance self-cleaning vacuum pump that requires less maintenance and reduces the standard service time by 4 minutes!



Features

R134A.

Fully recover and recharge in any climatic condition.

ECONOMICAL.

Long life pump functionality that performs a self-cleaning process reducing maintenance.

ADDITIONAL PRESSURE SENSOR.

Equipped with an additional pressure sensor for faster air purge.

HYBRID FUNCTION.

Designed for servicing all passenger cars, trucks, and hybrid vehicles (ACX1120H/1150H only).

TIME SAVING PERFORMANCE.

High performance vacuum pump to ensure faster service times, 4 minutes less than a double-capacity pump.

UPGRADED FILTER.

A larger capacity filter increases efficiency and decreases service time.

AIR PURGE.

Automatic air purge maximizes efficiency, speed and ease of control process.

NEW SOFTWARE

Software upgrades enhance unit performance by removing the requirement for multi-pass.

ECO LOCK QUICK COUPLERS.

Engineered to prevent gas dispersion into the environment.



ECO LOCK
Quick
Couplers



**Have questions about products?
Or want to find a distributor?**

Contact Customer Service Department at
800-468-2321 or **sales.mss@us.mahle.com**

Visit us at **www.servicesolutions.mahle.com**

ArcticPRO®

Going Beyond Standards

FEATURE COMPARISON

| FEATURE | REFRIGERANT 134A | | | | | | REFRIGERANT 1234YF | |
|--|------------------|---------|----------|---------|----------|----------|--------------------|---------|
| | ACX1120H | ACX1150 | ACX1150H | ACX1180 | ACX1180C | ACX1180H | ACX1250 | ACX1280 |
| Fully-Automatic | * | * | * | * | * | * | * | * |
| Multi-lingual Display | * | * | * | * | * | * | * | * |
| 2-Year Warranty | * | * | * | * | * | * | * | * |
| High & Low Side Refrigerant Charging | * | * | * | * | * | * | * | * |
| Vacuum Leak Test | * | * | * | * | * | * | * | * |
| Notification Alarm | * | * | * | * | * | * | * | * |
| Refrigerant & Filter Management | * | * | * | * | * | * | * | * |
| Automatic Oil Drain | * | * | * | * | * | * | * | * |
| Automatic Air Purge | * | * | * | * | * | * | * | * |
| ECO LOCK® Quick Couplers | * | * | * | ● | ● | ● | * | ● |
| Included Database | N/A | ● | ● | ● | ● | ● | | |
| On-board Integrated Thermal Printer | ● | ● | ● | ● | * | ● | ● | * |
| Remote Technical Support and Service | * | * | * | | | | * | |
| Integrated Hose Flushing (H and C models only) | | | * | | * | * | * | * |
| External Hose Flushing Adapter | * | | | | | | | |
| Hybrid-Capable | * | | * | | * | * | * | |
| 5 CFM Vacuum Pump | | | | | * | | | * |
| 1.5 CFM Vacuum Pump | * | * | * | * | | * | * | |
| Shock-Mounted Load Cell | | | | * | * | * | | * |
| Integrated Identifier | | | | ● | ● | ● | | * |
| External Identifier | | | | | | | * | |
| Temp Probes with 20' Cables | | | | | * | | | |
| Factory-Installed Heater Belt | | | | | * | | | |
| Automatic Dye Injection | | * | | | ● | | | |
| 50-lb Internal Cylinder | | | | | * | | | |
| Touch Screen | | 4.3" | 4.3" | | | | 4.3" | |

*-INCLUDED ●-OPTIONAL N/A- NOT AVAILABLE