


MAHLE

Driven by performance

FORKLIFT JACKS



Heavy duty forklift jacks that have set the industry standard for forklift jacks for over 40 years.

www.servicesolutions.mahle.com

ShopPRO[®]

4 Ton & 7.5 Ton Forklift Jacks

These heavy duty forklift jacks feature a two position lift pad that easily adjusts to handle flat-edged surfaces and have set the industry standard for forklift jacks for over 40 years.

FEATURES:

- Two position lift pad that easily adjusts to handle flat or edged surfaces
- Low starting height of 2¼" allows maximum flexibility
- Hold-to-Run™ release knob provides a slow descent rate with precise operator control
- *Air/Hydraulic powered models available!*

- 485 80087 00 **CFL-7 7.5 Ton Forklift Jack**
- 485 80088 00 **CFL-7A 7.5 Ton Forklift Jack – Air Assist**
- 485 80085 00 **CFL-4 4 Ton Forklift Jack**
- 485 80086 00 **CFL-4A 4 Ton Forklift Jack – Air Assist**

FEATURE COMPARISON	CFL-4	CFL-4A	CFL-7	CFL-7A
Capacity	8,000 lb (3,629 kg)	8,000 lb (3,629 kg)	15,442 lb (7,004 kg)	15,442 lb (7,004 kg)
Maximum Lift Height	16 in (41 cm)	16 in (41 cm)	16 in (41 cm)	16 in (41 cm)
Power	Hydraulic	Air/Hydraulic	Hydraulic	Air/Hydraulic
Required Air Pressure	N/A	155 psi (10.7 bar)	N/A	
Reach (Raised Position)	7 in (18 cm)	7 in (18 cm)	7 in (18 cm)	7 in (18 cm)
Distance from Hydraulic Cylinder to Lift Pad:				
Width	8 in (20 cm)	8 in (20 cm)	10 in (25 cm)	10 in (25 cm)
Starting Pad Height (Lift Arm Noch)	2.3 in (5.8 cm)	2.3 in (5.8 cm)	2.3 in (5.8 cm)	2.3 in (5.8 cm)
Starting Pad Height (Serrated Lift Pad)	2.5 in (6.3 cm)	2.5 in (6.3 cm)	2.5 in (6.3 cm)	2.5 in (6.3 cm)
Shipping Weight	68 lb (31 kg)	71 lb (32 kg)	93 lb (42 kg)	98 lb (44 kg)