## **Standard Brake Lathe Accessories**

The RTI BRC35 is caliper-mounted, ensuring that the machined rotor surface will be virtually parallel to the disc brake pad plane. This and the microfinish, created by the BRC35's variable feed and speed, guarantees the maximum contact of brake pad to rotor surface area possible. Run-out, brake squeal, pedal pulsation, and adverse steering symptoms are eliminated. Brake performance is enhanced and comebacks are eliminated. No other lathe at any price offers so much precision!

In addition to the Lathe Head and the Hub Drive Motor, the following standard Accessories are part of the BRC35 package:

Description	Quantity	Description	Quantity
Handle	1	Bolt (8 mm) (70 mm lg.)	2
Twin Cylinder Clamp (80 mm)	2	Bolt (10 mm) (70 mm lg.)	2
Silencer Band	1	Threaded Adapter #3	2
Hex Key Wrench (6 mm)	1	Threaded Adapter #5	2
Hex Key Wrench (8 mm)	1	Threaded Adapter #9	2
Mounting Spacer	6	Threaded Adapter #44	2
Threaded Bar	2	Threaded Adapter #48	2
S-Hook	2	Threaded Adapter #60	2
Power Cable	1	Carrying case	1
Hollow Adapter (48 mm lg.)	2		

## **Brake Lathe Technical Specifications**

Lathe:		Stand and geared motor:	
Weight:	18 lbs. (8 kg)	Weight:	56 lbs. (25 kg)
Max disc		Height:	16" to 48" (41 cm-122 cm)
capacity:		Hub drive speed:	60 RPM or 120 RPM
Diameter	No practical limit	Hub drive	.5 HP
Stroke	3.35" (85 mm)	motor:	
Thickness	1.57" (40 mm)	Electrical:	115V, 60Hz (USA)
Cut adjustment:	.002" (0.05 mm) per		220-240V, 50-60Hz
Cut adjustment:	division		(export)
Variable feed	.002" to .009" per rotor	U.S. Patents:	5,499,563;

rate:	revolution	5,549,023
Feed motor:	12 volt D.C.	
Cutting tips:	Positive rake carbide with 3 edges	

## **Popular Brake Lathe Accessories**

The standard RTI BRC35 includes the adapters necessary for most general repair operations focusing on front brakes of front-drive cars with pre-loaded wheel bearings. Additional adapters may be desired if the BRC35 is to be used on 4WD and rear wheel drive vehicles. RTI recommends that only genuine RTI cutting tools be used for best results. Information in regards to other service/repair parts is available by contacting RTI's Technical Support Department.

Cutting Tools 10 Pack Negative Rake	P/N 080-80000-68
Package of 10 Negative Rake Cutting tips for BRC35 units having	
black tool holders.	
Cutting Tools 10 Pack Positive Rake	P/N 080-80102-00
Package of 10 Positive Rake Cutting tips for BRC35 units having	
silver tool holders.	
Twin Cylinder Mounting Clamp 100 mm	P/N 080-80000-11
Extra long clamp, useful for some rear brake applications to allow	
unit to more easily clear wheel wells. Also needed for some 4WD	
applications.	

Ford Adapter F150 Type	P/N 080-80000-70
Special adapter that mounts to Ford "sliding caliper" designs in light- medium duty trucks.	

Ford Adapter F350 Type	P/N 080-80000-74
Special adapter that mounts to Ford "sliding caliper" designs on heavier duty trucks.	

GM Adapter ''W'' Body	P/N 080-80000-82
Adapter specially designed by RTI to allow on-the-car turning on	
"W" body GM cars with composite rotors and stamped steel steering	
knuckles. Turning these rotors on a bench lathe with good results is	
difficult. The adapter provides a high degree of rigidity allowing	
good results with the BRC35 as long as the axle bearings are not	
worn to a point where bearing pre-load is below spec.	
Wheel Drive Brackets Extended	P/N 080-80000-81
Larger legs allow connection to larger diameter bolt circles used in	
medium duty trucks, and allows clearance for most larger 4WD	
hubs. 2 required.	

Adapter Kit Toyota Full Coverage	P/N 380-80017-00
Includes additional adapters for Toyota 4WD and late model Previa.	
Includes (2) 100mm long Twin Cylinder Mounting Clamps and	
Extended Wheel Drive Brackets. Standard BRC35 includes adapters	
for Toyota cars.	

Adapter Kit Deluxe Full Coverage	P/N 380-80008-01
Includes threaded 8mm adapter for high volume operations that	
prefer this design over standard hollow pin set-up. Includes 7/16"	
threaded adapter for Ford rear wheel drive applications. Also	
includes contents of Toyota Full Coverage Kit as well as Ford F150	
and GM "W" Body adapters. 10 pack of positive rake cutting tools	
included. This should be ordered for shops buying the BRC35 that	
want maximum coverage.	

Lifting Spring Kit	P/N 380-80020-00
Special kit with gas charged spring to counterweight and assist	
movement of BRC35's Power Drive Unit. Fits newest "slot" type	
adjustment stands. Field installation without special tools. Will also	
fit older type stands with some minor modification.	

Dial Indicator Set Central Tool 6624 Precision Gauge for Run- out	
Made by a leading manufacturer to RTI's specifications. Uses a "vice	

grip" clamp and adjustable "goose neck" type stand for mounting. Dial indicator is graduated to allow precise readings of tenthousands of an inch. A necessary tool for precision brake machining and as a sales tool to justify the need for on-the-car TI BRC35. P/N 080-80103-00

## **Demo/Training Stand w/Chip Tray**

Vibration/Noise Dampener

Special heavy-duty tripod stand, easily disassembled for transport. Includes Ford Tempo/Escort Steering Knuckle, Wheel Bearing and Hub. Rotor not included. Recommended for distributor sales professionals in selling/training. Also recommended for larger shops in on-going training of new technicians. The BRC35's operation can be easily and quickly learned, especially by technicians already experienced in the use of a bench lathe. However, the patented adjustability of the RTI BRC35, with variable feed and speed is best learned initially through practice on a demo/training stand so as to realize the full potential of the BRC35's superior capability. This item can be rented from RTI by contacting RTI's Technical Support Department.

A simple elastic 3/8" wide dampener is supplied with the BRC35. Replacements are available as a service part. Almost any of the many types and brands of commercially available dampeners are acceptable according to the shop and technician's preference. P/N 380-80007-00

P/N 080-80000-04

Everything you need for on-the-car brake service.