PSX-1Power Steering Fluid Exchanger

Offer power steering fluid exchange service with this fast, reliable and easy to operate machine.

- Multi-fluid capability—quick and easy changeover between different power steering fluid types
- ◆ Fast, accurate, dual pump operation
- ◆ Quick and profitable, complete service time averages 5 – 10 minutes
- Provides professional, thorough exchange of fluid
- Easy service hook-up—direct interface with power steering fluid reservoir
- ◆ Easy mobility—4 durable, swivel casters
- Simple operation—just flip a switch and begin extracting or adding fluid
- High quality, positive displacement diaphragm pumps require no priming, and are designed for years of operation

- Available for bench-top mount (use your workbency or cart)
- ◆ Available to mount ot existing ATX-2 unit
- Clear two-channel hose, provides excellent new versus used fluid visual
- Convenient shelf for storage and small footprint saves valuable shop space
- Professional appearance helps sell legitimate OEM recommended service
- Clean operation—hose end caps prevent fluid spill
- ◆ Lifetime toll-free tech support
- One year warranty

Specifications	
Electrical:	12V DC 4.0 amps
Dimensions:	45"H x 22"W x 21"D (114cm x 56cm x 53cm)
Weight:	35 Lbs (16 Kg)
Operating Range:	32°F to 122°F (0°C to 50°C)
New Fluid Pump:	Diaphragm type – 1.0 gpm (3.79 lpm)
Used Fluid Pump:	Diaphragm type — 1.0 gpm (3.79 lpm)
Hoses:	3/8" Clear PVC (.95 cm)
New Tank:	1.0 gallon clear PVC (3.79 liters)
Used Tank:	1.0 gallon clear PVC (3.79 liters)
Process Time:	5 – 10 minutes average
Fluid Types:	Multiple fluid capability
Casters:	360° Swivel; locking

PSX-1	(Bench-mount)
PSX-1	(ATX-mount)

P/N 415-80002-00 P/N 415-80004-00

Minor assembly required.

ATX-2PS Combo Power Steering/Transmission Service Unit (ATX-2 and PSX-1 Combo)



