SC-10FP

The Strut Spring Compressors for MacPherson Struts save time, work, and money.

The special plasti-coated forged jaws are designed to fit securely around the spring and protect the spring from damage. The built-in safety lip prevents slipping.

Two pairs of easy fitting jaws are standard accessories, covering spring diameters of 80-200 mm (3.1-7.8 inches). The jaws are locked onto the compressor body with the enclosed screws that must be mounted on the tool for operation. A standard heavyduty wrench allows rapid jaw interchange. A built-in shear pin prevents overload.

The unit is rated for 2000 pounds and can be used "on-the-car" or "off-the-car." It is highly portable and can be operated with an air wrench. The SC-15FP is identical to the SC-10FP except it comes with a wall mount bracket that doubles as a safety cage.

1 Year limited warranty covering all defects, except those caused by misuse or abuse.

Compressor: Weight — 9.6 pounds (4.3 Kg); Length — 19 inches (483 mm); Width — 2.4 inches (61 mm); Depth — 3.5 inches (89 mm).

Strut Spring Coverage: Small Jaws — 2.1 pounds (0.95 Kg), 3.1-6.5 inches (80-165 mm); Large Jaws — 2.9 pounds (1.3 Kg), 6.1-7.8 inches (155-200 mm).

SC-10FP P/N 485-80001-00 SC-15FP P/N 485-80003-00

Optional Accessories:

Micro Jaws (2 required) 2.7-3.9 inches (70-100 mm) P/N 085-80002-00

Mega Jaw (1 required) 7.0-9.2 inches (180-235mm) P/N 085-80001-00



SC-15FP